



**SPECIFICATION**

- Light Source LED Module (Mounted)
- Light Distribution W=Wide
- Cone White Cone(WC), Matte Black Cone(MC)  
Chrome Cone(CC)
- Frame White(SWF),Matte black(SMF)
- Approved Driver Constant current (Sold Separately)
- Fixture Input Voltage 35.8V
- Fixture Input Current 0.9A MAX
- Weight 690g
- Attached Safety Wire

**製品コード**

MMP-100F/WC/SWF/W/30B27/DL/3  
MMP-100F/WC/SWF/W/30B30/DL/3  
MMP-100F/WC/SWF/W/30B35/DL/3  
MMP-100F/WC/SWF/W/30B40/DL/3  
  
MMP-100F/MC/SWF・SMF/W/30B27/DL/3  
MMP-100F/MC/SWF・SMF/W/30B30/DL/3  
MMP-100F/MC/SWF・SMF/W/30B35/DL/3  
MMP-100F/MC/SWF・SMF/W/30B40/DL/3  
  
MMP-100F/CC/SWF・SMF/W/30B27/DL/3  
MMP-100F/CC/SWF・SMF/W/30B30/DL/3  
MMP-100F/CC/SWF・SMF/W/30B35/DL/3  
MMP-100F/CC/SWF・SMF/W/30B40/DL/3



	PARTS	MATERIAL	REMARK
1	Socket Holder	ADC	Acrylic Baking Finish
2	LED Module		
3	Reflector	Aluminum	
4	Body	ADC	Acrylic Baking Finish
5	Glare Cut Ring	ADC	
6	Cone	ADC	WC,MC:Acrylic Baking Finish CC:Plating Finish
7	Unit Mounting Spring	ADC	Acrylic Baking Finish
8	Body	ADC	Acrylic Baking Finish
9	Safety Wire	Stainless Steel	
10	Safety Connector	Resin	

**ATTENTION**

- Use within 0℃~35℃ ambient temperature range
- Do not cover fixtures with the heat insulator etc.
- Keep distance of the fixtures and objects 0.2m or more.
- Danger ! Do not remodel fixtures.
- Do not use a radio or TV near the fixtures. The unit may generate noise in the radio or TV.
- Connect a safety wire to the fixture and mounting frame directly.
- Emission color and brightness would be different even within the same model.
- Use the constant current driver only.
- Connect input-side power wire to the Approved driver directly.
- Please do not remove safety connector