


SPECIFICATION

- Light Source LED Module (Mounted)
- Frame White(SWF), Matte Black(SMF)
- Cone White Cone(WC), Matte Black Cone(MC)
Chrome Cone(CC)
- Approved Driver Constant current (Sold Separately)
- Fixture Input Voltage 36. 8V
- Fixture Input Current 0. 7A MAX
- Weight 490g
- Attached Safety Wire

PRODUCT CODE

MMP-080W/WC/SWF/O/20B27/DL/3
 MMP-080W/WC/SWF/O/20B30/DL/3
 MMP-080W/WC/SWF/O/20B35/DL/3
 MMP-080W/WC/SWF/O/20B40/DL/3
 MMP-080W/MC/SWF・SMF/O/20B27/DL/3
 MMP-080W/MC/SWF・SMF/O/20B30/DL/3
 MMP-080W/MC/SWF・SMF/O/20B35/DL/3
 MMP-080W/MC/SWF・SMF/O/20B40/DL/3
 MMP-080W/CC/SWF・SMF/O/20B27/DL/3
 MMP-080W/CC/SWF・SMF/O/20B30/DL/3
 MMP-080W/CC/SWF・SMF/O/20B35/DL/3
 MMP-080W/CC/SWF・SMF/O/20B40/DL/3



Ceiling Hole Diameter

	PARTS	MATERIAL	REMARK
1	Socket Holder	ADC	Acrylic Baking Finish
2	LCL Fixture	ADC	Acrylic Baking Finish
3	Body	ADC	Acrylic Baking Finish
4	LED Module		
5	Reflector	Aluminum	
6	Unit Mounting Spring	Stainless Steel	
7	Mounting Frame	ADC	Acrylic Baking Finish
8	Cone	ADC	Acrylic Baking Finish(WC・MC) Plating Finish(CC)
9	Cone Cover	ADC	Acrylic Baking Finish(WC・MC) Plating Finish(CC)
10	Lens Filter	Hard Glass	
11	Safety Wire	Stainless Steel	
12	Safety Connector	Resin	

ATTENTION

- Do not cover fixtures with the heat insulator etc.
- Please use constant current driver.
- Connect input-side power wire to the approved driver directly.
- Danger! Do not remodel fixtures.
- Use within 0℃~35℃ ambient temperature range
- Connect a safety wire to the fixture and mounting frame directly.
- Emission color and brightness would be different even within the same model.
- Keep distance of the fixtures and objects 0. 1m or more.
- Please do not remove safety connector