


**Discontinued product**




**SPECIFICATION**

- Light Source LED Module (Mounted)
- Light Distribution M=Medium
- Cone White Cone(WC)  
Matte Black Cone(MC)  
Chrome Cone(CC)
- Vertical aiming angle 30°
- Dedicated Driver Constant current ( 50/60Hz shared)
- Fixture Input Voltage 37. 8V
- Fixture Input Current 0. 9A (MAX)
- Weight 570g
- Safety Wire Attached

**PRODUCT CODE**

- MSP-100A/WC/FLF/M/30B27/DL/3
- MSP-100A/WC/FLF/M/30B30/DL/3
- MSP-100A/WC/FLF/M/30B35/DL/3
- MSP-100A/WC/FLF/M/30B40/DL/3
- MSP-100A/MC/FLF/M/30B27/DL/3
- MSP-100A/MC/FLF/M/30B30/DL/3
- MSP-100A/MC/FLF/M/30B35/DL/3
- MSP-100A/MC/FLF/M/30B40/DL/3
- MSP-100A/CC/FLF/M/30B27/DL/3
- MSP-100A/CC/FLF/M/30B30/DL/3
- MSP-100A/CC/FLF/M/30B35/DL/3
- MSP-100A/CC/FLF/M/30B40/DL/3

(mm)



	PARTS	MATERIAL	REMARK
1	Body	ADC	Acrylic Baking Finish
2	LED Module	_____	_____
3	Reflector	Aluminum	_____
4	Reflector fixing bracket	Aluminum	Material Origin Color
5	Hood	ADC	Acrylic Baking Finish
6	Cone	ADC	Acrylic Baking Finish(WC·MC) Plating Finish(CC)
7	Safety Wire	Stainless Steel	_____
8	Safety Connector	Resin	_____

**ATTENTION**

- Emission color and brightness would be different even within the same model.
  - Danger! Do not remodel fixtures.
  - Do not cover fixtures with the heat insulator etc.
  - Keep distance of the fixtures and objects 0. 2m or more.
  - Use within 0℃~35℃ ambient temperature range.
  - Connect a safety wire to the fixture and mounting frame directly.
  - Please use constant current driver.
  - Connect input-side power wire to the approved driver directly.
  - Please do not remove safety connector
  - Please do not plug in the wrong electrode to the applicable driver.
- It may cause shortening of LED lifetime or the damage to the LED component.
- This equipment is a ceiling installation exclusive equipment. It can not be mounted on an inclined ceiling or wall.
  - Please use the "class2" driver. In that case, grounding is not required.

<p><b>ModuleX</b> ModuleX Inc.</p>	<p>SPECIFICATION SHEET</p>	SCALE	CREATED DATE	REVISION DATE
		1 / 3	1/APR/2020	