

SERIES


**ModuleX®100**

FUNCTION

FOUNDATION down light

CAT, No.

MSP-100F/CC/SWF・SMF/M・F/30B/DL/3




**SPECIFICATION**

- Light Source LED Module (Mounted)
- Light Distribution M=Medium, F=Flood
- Mounting Frame White(SWF), Matte Black(SMF)
- Cone Color Chrome Cone(CC)
- Dedicated Driver Constant current (Sold Separately)
- Fixture Input Voltage 37.8V
- Fixture Input Current 0.9A MAX
- Weight 420g
- Attached Safety Wire

**PRODUCT CODE**

MSP-100F/CC/SWF・SMF/M・F/30B27/DL/3  
MSP-100F/CC/SWF・SMF/M・F/30B30/DL/3  
MSP-100F/CC/SWF・SMF/M・F/30B35/DL/3  
MSP-100F/CC/SWF・SMF/M・F/30B40/DL/3



	PARTS	MATERIAL	REMARK
1	Body	ADC	Acrylic Baking Finish
2	LED Module		
3	Reflector	Aluminum	
4	Cone	ADC	Plating Finish
5	Filter	Resin	
6	Packing	EPT Sponge	Black
7	Mounting Frame	ADC	Acrylic Baking Finish
8	Unit Mounting Spring	Stainless Steel	
9	Safety Wire	Stainless Steel	
10	Safety Connector	Resin	

**ATTENTION**

- Use within 0℃~35℃ ambient temperature range.
- Do not cover fixtures with the heat insulator etc.
- Keep distance of the fixtures and objects 0.2m or more.
- Danger ! Do not remodel fixtures.
- Connect a safety wire to the fixture and mounting frame directly.
- Emission color and brightness would be different even within the same model.
- Please use constant current driver.
- Connect input-side power wire to the approved driver directly.
- Please do not remove safety connector
- Please do not plug in the wrong electrode to the applicable driver.
- It may cause shortening of LED lifetime or the damage to the LED component.
- This equipment is a ceiling installation exclusive equipment. It can not be mounted on an inclined ceiling or wall.

**ModuleX**  
ModuleX Inc.

SPECIFICATION SHEET

SCALE  
1/3

CREATED DATE  
17/APR/2017

REVISION DATE