

SERIES


**ModuleX®80**

FUNCTION

FOUNDATION downlight

CAT, No.

SL-B1351D/CE/WC




**SPECIFICATION**

- Light Source LED Module (Mounted)
- Light Distribution W=Wide, M=Medium
- Cone Color White Cone(WC)
- Approved Driver Constant current (Sold Separately)
- Fixture Input Voltage 38. 6V
- Fixture Input Current 0. 7A MAX
- Weight 290g
- Attached Safety Wire

**PRODUCT CODE**

SL-B1351D/CE/W/R24B/WC  
 SL-B1351D/CE/W/R27B/WC  
 SL-B1351D/CE/W/R30B/WC  
 SL-B1351D/CE/W/R35B/WC  
 SL-B1351D/CE/W/R40B/WC  
 SL-B1351D/CE/M/R24B/WC  
 SL-B1351D/CE/M/R27B/WC  
 SL-B1351D/CE/M/R30B/WC  
 SL-B1351D/CE/M/R35B/WC  
 SL-B1351D/CE/M/R40B/WC



	PARTS	MATERIAL	REMARK
1	Socket Holder	ADC	Acrylic Baking Finish
2	LED Module		
3	Body	ADC	Acrylic Baking Finish
4	Reflector	Aluminum	
5	Lens Filter	Hard Glass	Stationary type
6	Cone	ADC	Acrylic Baking Finish
7	Safety Wire	Stainless Steel	
8	Safety Connector	Resin	

**ATTENTION**

- Do not cover fixtures with the heat insulator etc.
- Please use constant current driver.
- Connect input-side power wire to the approved driver directly.
- Danger! Do not remodel fixtures.
- Use within 0℃~35℃ ambient temperature range
- Connect a safety wire to the fixture and mounting frame directly.
- Emission color and brightness would be different even within the same model.
- Keep distance of the fixtures and objects 0. 1m or more.
- Please do not remove safety connector

**ModuleX**

ModuleX Inc.

SPECIFICATION SHEET

SCALE

1 / 2

CREATED DATE

28/12/2017

REVISION DATE