

SERIES


ModuleX®80

FUNCTION

FOUNDATION down light

CAT. No.

SL-B1352D/CE/N/WC・NC




SPECIFICATION

- Light source LED Module (Installed)
- Light Distribution N=Narrow
- Cone White Cone (WC)・Natural Cone (NC)
- Approved Driver Constant current (Sold separately)
- Fixture Input Voltage 19.5V
- Fixture Input Current 0.7A
- Weight 250g
- Attached Safety Wire

PRODUCT CODE

SL-B1352D/CE/N/R24B/WC・NC
 SL-B1352D/CE/N/R27B/WC・NC
 SL-B1352D/CE/N/R30B/WC・NC
 SL-B1352D/CE/N/R35B/WC・NC
 SL-B1352D/CE/N/R40B/WC・NC



| | PARTS | MATERIAL | REMARK |
|---|-------------------|-----------------|---|
| 1 | Heat Conduct Body | ADC | Acrylic Baking Finish |
| 2 | Body | ADC | Acrylic Baking Finish |
| 3 | Adapter | ADC | Acrylic Baking Finish |
| 4 | Cone | ADC | WC:Acrylic Baking Finish NC:Plating Finish |
| 5 | Safety Wire | Stainless Steel | |
| 6 | Safety Connector | Resin | |

ATTENTION

- Do not cover fixtures with the heat insulator etc.
- Please use constant current driver.
- Connect input-side power wire to the approved driver directly.
- Danger! Do not remodel fixtures.
- Use within 0℃~35℃ ambient temperature range
- Connect a safety wire to the fixture and mounting frame directly.
- Emission color and brightness would be different even within the same model.
- Keep distance of the fixtures and objects 0.1m or more.
- Please do not remove safety connector

ModuleX

ModuleX Inc.

SPECIFICATION SHEET

SCALE

1/2

CREATED DATE

28/12/2017

REVISION DATE