

SERIES


ModuleX®80

FUNCTION

FOUNDATION down light

CAT, No.

SX-B1352D/CE/BF




SPECIFICATION

- Light source LED Module (Installed)
- Frame White(W), Matte Black(M)
- Light Distribution M=Medium, W=Wide, SP=Rectangle
- Cone Black Baffle Cone(BF)
- Approved Driver Constant current (Sold separately)
- Fixture Input Voltage 19.5V
- Fixture Input Current 0.7A
- Weight 310g
- Attached Safety Wire

PRODUCT CODE

SX-B1352D/CE/M·W·SP/R24B/BF/W·M
 SX-B1352D/CE/M·W·SP/R27B/BF/W·M
 SX-B1352D/CE/M·W·SP/R30B/BF/W·M
 SX-B1352D/CE/M·W·SP/R35B/BF/W·M
 SX-B1352D/CE/M·W·SP/R40B/BF/W·M



	PARTS	MATERIAL	REMARK
1	Heat Conduct Body	ADC	Acrylic Baking Finish
2	Body	ADC	Acrylic Baking Finish
3	Adapter	ADC	Acrylic Baking Finish
4	Lens Filter	Hard Glass	M·W·SP
5	Unit Mounting Spring	Stainless Steel	
6	Mounting Frame	ADC	Acrylic Baking Finish
7	Cone	ADC	Acrylic Baking Finish
8	Safety Wire	Stainless Steel	
9	Safety Connector	Resin	

ATTENTION

- Do not cover fixtures with the heat insulator etc.
- Please use constant current driver.
- Connect input-side power wire to the approved driver directly.
- Danger! Do not remodel fixtures.
- Use within 0℃~35℃ ambient temperature range
- Connect a safety wire to the fixture and mounting frame directly.
- Emission color and brightness would be different even within the same model.
- Keep distance of the fixtures and objects 0.1m or more.
- Please do not remove safety connector

ModuleX®

ModuleX Inc.

SPECIFICATION SHEET

SCALE

1/2

CREATED DATE

28/12/2017

REVISION DATE