

SERIES


**ModuleX®80**

FUNCTION

FOUNDATION down light

CAT, No.

SX-B1352D/CE/N/BF




**SPECIFICATION**

- Light source LED Module (Installed)
- Frame White(W), Matte Black(M)
- Light Distribution N-Narrow
- Cone Black Baffle Cone(BF)
- Approved Driver Constant current (Sold separately)
- Fixture Input Voltage 19.5V
- Fixture Input Current 0.7A
- Weight 310g
- Attached Safety Wire

**PRODUCT CODE**

SX-B1352D/CE/N/R24B/BF/W・M  
 SX-B1352D/CE/N/R27B/BF/W・M  
 SX-B1352D/CE/N/R30B/BF/W・M  
 SX-B1352D/CE/N/R35B/BF/W・M  
 SX-B1352D/CE/N/R40B/BF/W・M



	PARTS	MATERIAL	REMARK
1	Heat Conduct Body	ADC	Acrylic Baking Finish
2	Body	ADC	Acrylic Baking Finish
3	Adapter	ADC	Acrylic Baking Finish
4	Unit Mounting Spring	Stainless Steel	
5	Mounting Frame	ADC	Acrylic Baking Finish
6	Cone	ADC	Acrylic Baking Finish
7	Safety Wire	Stainless Steel	
8	Safety Connector	Resin	

**ATTENTION**

- Do not cover fixtures with the heat insulator etc.
- Please use constant current driver.
- Connect input-side power wire to the approved driver directly.
- Danger! Do not remodel fixtures.
- Use within 0℃~35℃ ambient temperature range
- Connect a safety wire to the fixture and mounting frame directly.
- Emission color and brightness would be different even within the same model.
- Keep distance of the fixtures and objects 0.1m or more.
- Please do not remove safety connector

**ModuleX®**

ModuleX Inc.

SPECIFICATION SHEET

SCALE

1/2

CREATED DATE

28/12/2017

REVISION DATE