

SERIES


**ModuleX°100**

FUNCTION

FOUNDATION downlight

CAT, No.

SX-B9351D/CE/WC, MC




**SPECIFICATION**

- Light Source LED Module (Mounted)
- Light Distribution W=Wide, M=Medium
- Cone Color White Cone(WC)  
Matte Black Cone(MC)
- Frame White, Matte Black
- Approved Driver Constant current (Sold Separately)
- Fixture Input Voltage 38, 6V
- Fixture Input Current 0.7A MAX
- Weight 570g
- Safety Wire Attached

**PRODUCT CODE**

SX-B9351D/CE/M/R27B/WC/W SX-B9351D/CE/M/R27B/MC/W·M  
 SX-B9351D/CE/M/R30B/WC/W SX-B9351D/CE/M/R30B/MC/W·M  
 SX-B9351D/CE/M/R35B/WC/W SX-B9351D/CE/M/R35B/MC/W·M  
 SX-B9351D/CE/M/R40B/WC/W SX-B9351D/CE/M/R40B/MC/W·M  
 SX-B9351D/CE/W/R27B/WC/W SX-B9351D/CE/W/R27B/MC/W·M  
 SX-B9351D/CE/W/R30B/WC/W SX-B9351D/CE/W/R30B/MC/W·M  
 SX-B9351D/CE/W/R35B/WC/W SX-B9351D/CE/W/R35B/MC/W·M  
 SX-B9351D/CE/W/R40B/WC/W SX-B9351D/CE/W/R40B/MC/W·M

Unit: mm



	PARTS	MATERIAL	REMARK
1	Socket Holder	ADC	
2	LED Module		
3	Body	ADC	
4	Reflector	Aluminium	
5	Filter fixing bracket	Steel Plate	Acrylic Baking Finish
6	Unit Mounting Spring	Stainless Steel	
7	Mounting Frame	ADC	Acrylic Baking Finish
8	Cone	ADC	Acrylic Baking Finish
9	Lens Filter	Hardened Glass	
10	Safety Wire	Stainless Steel	
11	Safety Connector	Resin	

**ATTENTION**

- Emission color and brightness would be different even within the same model.
- Danger! Do not remodel fixtures.
- Do not cover fixtures with the heat insulator etc.
- Keep distance of the fixtures and objects 0.2m or more.
- Use within 0℃~35℃ ambient temperature range.
- Connect a safety wire to the fixture and mounting frame directly.
- Please use constant current driver.
- Connect input-side power wire to the approved driver directly.
- Please do not remove safety connector
- This equipment is a ceiling installation exclusive equipment. It can not be mounted on an inclined ceiling or wall.

**ModuleX°**  
ModuleX Inc.

SPECIFICATION SHEET

SCALE

1/3

CREATED DATE

28/12/2017

REVISION DATE