


**SPECIFICATION**

- Frame White, Matte Black
- Cone White Cone(WC), Matte Black Cone(MC), Natural Cone(NC)
- Approved Driver Constant current (Sold separately)
- Fixture Input Voltage 37.6V
- Fixture Input Current 0.7A MAX
- Weight 750g
- Attached Safety Wire

**PRODUCT CODE**

SX-B9451D/V2/CE/R27B/WC/W  
 SX-B9451D/V2/CE/R27B/MC/W·M  
 SX-B9451D/V2/CE/R27B/NC/W·M  
 SX-B9451D/V2/CE/R30B/WC/W  
 SX-B9451D/V2/CE/R30B/MC/W·M  
 SX-B9451D/V2/CE/R30B/NC/W·M  
 SX-B9451D/V2/CE/R35B/WC/W  
 SX-B9451D/V2/CE/R35B/MC/W·M  
 SX-B9451D/V2/CE/R35B/NC/W·M  
 SX-B9451D/V2/CE/R40B/WC/W  
 SX-B9451D/V2/CE/R40B/MC/W·M  
 SX-B9451D/V2/CE/R40B/NC/W·M



	PARTS	MATERIAL	REMARK
1	Utility Socket	ADC	Acrylic Baking Finish
2	Body	ADC	Acrylic Baking Finish
3	LED Module	_____	_____
4	Cone	ADC	WC, MC: Acrylic Baking Finish NC: Plating Finish
5	Lens Filter	Hard Glass	Partial Shot Processing
6	Cone Cover	ADC	WC, MC: Acrylic Baking Finish NC: Plating Finish
7	Mounting Frame	ADC	Acrylic Baking Finish
8	Unit Mounting Spring	Stainless Steel	_____
9	Safety Wire	Stainless Steel	_____
10	Safety Connector	Resin	_____

- ATTENTION**
- Use within 0℃~35℃ ambient temperature range.
  - Do not cover fixtures with the heat insulator etc.
  - Connect a safety wire to the fixture and mounting frame directly
  - Emission color and brightness would be different even within the same model.
  - The height of inside the ceiling have to be 160mm or more to install the driver there.
  - Danger! Do not remodel fixtures.
  - Keep distance of the fixtures and objects 0.1m or more.
  - Connect input-side power wire to the approved driver directly.
  - Please use constant current driver.
  - Please do not remove safety connector