

SPECIFICATION

- Light Source LED Module (Mounted)
- Light Distribution N=Narrow, M=Medium
- Cone White Cone(WC)  
Matte Black Cone(MC)  
Natural Cone(NC)
- Approved Driver Constant current (Sold separately)
- Fixture Input Voltage 38.6V
- Fixture Input Current 0.7A MAX
- Weight 510g
- Attached Safety Wire


PRODUCT CODE

- SL-B9651H/CE/N·M/R27B/NC·MC·WC
- SL-B9651H/CE/N·M/R30B/NC·MC·WC
- SL-B9651H/CE/N·M/R35B/NC·MC·WC
- SL-B9651H/CE/N·M/R40B/NC·MC·WC

OPTION (1 filter attachable)

- Diffusion Lens SA-3DL03
  - Wide Diffusion Lens SA-3DF01
  - Spread Lens SA-3SP01
  - Honeycomb Louver SA-3HC02
  - Conversion Filter SA-3CV02-03
  - Edge control Filter SA-3EC01
  - Sharpener SA-3SH01
- (available only for narrow distribution)

Unit: mm



PARTS	MATERIAL	REMARK
1 Socket Holder	ADC	Material-Origin Color
2 LED Module	_____	_____
3 Body	ADC	Material-Origin Color
4 Reflector	Aluminum	_____
5 Attachment Ring	ADC	Acrylic Baking Finish
6 Hood	ADC	Acrylic Baking Finish
7 Cone	ADC	Acrylic Baking Finish(WC·DC) Plating Finish(NC)
8 Joint	Stainless Steel	_____
9 Arm	Steel Plate	_____
10 Safety Wire	Stainless Steel	_____
11 Safety Connector	Resin	_____

**ATTENTION**

- Emission color and brightness would be different even within the same model.
- Danger! Do not remodel fixtures.
- Do not cover fixtures with the heat insulator etc.
- Keep distance of the fixtures and objects 0.2m or more.
- Use within 0°C~35°C ambient temperature range.
- Remove the hood downward.
- Connect a safety wire to the fixture and mounting frame directly.
- Please use constant current driver.
- Connect input-side power wire to the approved driver directly.
- Please do not remove safety connector.