



MMP-060S/5H/FC/10A/Z2/3

Installation Details	Installation Diagram • Caution
<p><b>Installation</b></p> <p>1 Open the <math>\phi 13</math> mm wire hole on the reinforced mounting surface and attach the mounting plate with the attached screws</p> <p>2 Align the protrusion of the mounting plate with the case mark and turn it clockwise until it clicks</p> <p>The mounting plate and the case are locked</p> <p>2' To unlock Push the included hexagonal wrench or the thin bar with a diameter of 2 mm or less into the case hole and turn the case counterclockwise</p>	<p>Dimensions of mounting plate</p> <p>Recommended wire opening diameter of mounting surface <math>\phi 13</math> mm</p>
<p>After installing the fixture, make sure that it is attached securely</p>	
<p>1 Connect the bundled dedicated Driver to the connector of Luminaire</p> <p>2 Please connect according to the description of the power supply.</p> <p>3 Install a dedicated driver on the ceiling</p>	<p>Wiring diagram</p> <p>NTC-SRP-2007-380-15CC</p> <p>LIGHTING FIXTURE</p> <p>0/1-10V Control Unit</p>
<p>Be sure to turn off the power before working</p> <p>Connect the connector securely. If you remove it pull while holding the lock. Do not connect or disconnect the connector while the power is on. (Cause of trouble)</p> <p>Do not touch the metal terminals on the inside of the connector directly with your hands.</p>	
<p><b>Adjustment of irradiation direction</b></p> <p>1 Grasp the fixture and adjust the irradiation direction</p>	<p>Range of movement</p> <p>Direction of irradiation</p> <p>Do not expose instruments upwards It is dangerous because dust etc. will be heated and accumulated</p>
<p>Do not forcibly move beyond the movable range</p> <p>Please adjust the fixture after turning off the power and cooling the fixture</p>	

Installation Details	Installation Diagram • Caution
<p><b>Optional parts installation</b></p> <p>1 Turn around the hood.</p> <p>2 Pull out the hood from the body.</p> <p>3 Turn around the option holder, and put out.</p> <p>4 Put a filter in hood.</p> <p>5 Turn around the option holder, and put in.</p>	<p>UP to 2 FILTERS</p> <p>Sharpner lens</p> <p>OPTION HOLDER</p> <p>cut</p>
<p>Please attention that the sharpener lens is counted two pieces of filter lenses.</p> <p>Don't put in the filters than the rule number of pieces. Causes of falling and damage.</p> <p>To rotate the holder, please wear a flat head screwdriver at the cut.</p> <p>Align the markings of the hood and the body, please turn it clockwise until it clicks.</p>	
<p><b>Tilting angle setting</b></p> <p>1 Please loose a screw by the hexagonal wrench, and unrock.</p> <p>Please regulate a point of view to a scale.</p>	<p>Pan lock</p> <p>Tilt lock</p>
<p>Please use an attached hexagon wrench by all means.</p>	